

Mail.XML Version 25.1

System Messages Specification

May 20, 2022

Working Group Chair

Shawn Baldwin, WindowBook

Technical Director

Shariq Mirza, DTAC Associate, Assurety Consulting & Solutions

Editor

Shariq Mirza, DTAC Associate, Assurety Consulting & Solutions

Copyright (c) 2021 – Delivery Technology Advocacy Council (“DTAC”). All Rights Reserved.

Mail.dat is a registered trademark of DTAC

Mail.XML is a trademark of DTAC



Copyright and Legal Notices

© 2022 Delivery Technology Advocacy Council. All Rights Reserved.

Copyright 2022 – Delivery Technology Advocacy Council (“DTAC”) is the “Copyright Owner” of “Mail.XML®”. All rights reserved by the Copyright Owner under the laws of the United States, Belgium, the European Economic Community, and all states, domestic and foreign. This document may be downloaded and copied provided that all copies retain and display the copyright and any other proprietary notices contained in this document. This document may not be sold, modified, edited, or taken out of context such that it creates a false or misleading statement or impression as to the purpose or use of the Mail.XML® specification, which is an open standard. Use of this Standard, in accord with the foregoing limited permission, shall not create for the user any rights in or to the copyright, which rights are exclusively reserved to the Copyright Owner.

DTAC and the members of the Mail.XML® Specifications - Committee (collectively and individually, "Presenters") make no representations or warranties, express or implied, including, but not limited to, warranties of merchantability, fitness for a particular purpose, title, or non-infringement. The presenters do not make any representation or warranty that the contents of this document are free from error, suitable for any purpose of any user, or that implementation of such contents will not infringe any third-party patents, copyrights, trademarks or other rights. By making use of this document, the user assumes all risks and waives all claims against Presenters.

In no event shall Presenters be liable to user (or other person) for direct, indirect, special or consequential damages arising from or related to any use of this document, including, without limitation, lost profits, business interruption, loss of programs, or other data on your information handling system even if Presenters are expressly advised of the possibility of such damages.

Some states do not allow the disclaimer or limitation of damages, so the disclaimers set forth above apply to the maximum extent permitted under applicable law.

Abstract

This document describes the messaging protocol for use by mailers and their consignees. The Mail.XML™ Transaction Protocol defines the roles and responsibilities of Shippers and Consignees and defines the format and method for message exchange. This messaging protocol is designed to be XML and Web-Services compliant.

Mail.XML and Mail.dat are trademarks of DTAC.

About Mail.XML™

Mail.XML™ is bringing a paradigm change to the industry by increasing business function specific B2B (Business to Business) communication within the industry that supports automation and in the end enables cost avoidance and higher profits through improved competence and effectiveness of communication. Mail.XML is designed to increase efficiency and lower costs by removing many manual data entry processes and enabling quick near real time communication between business partners. Mail.XML currently supports container based scheduling, pick up and drop off business processes, as well as identifying different business entities responsible for performing different services such as quality of mailing, address correction, and delivery confirmation on a mailing. The core focus of Mail.XML is communication between industry members and from industry to the final mail processing and delivery organization that delivers the mail to the end consumer, e.g., USPS. In the next few versions of Mail.XML the focus moves across mailing supply chain channels, and includes advanced functions such as payment; automated verification; enabling first, second, and third-party communication and incorporating presort planning, printing, and distribution processes.

About Mail.XML Schema Modularization

Today Mail.XML messages are grouped into 8 message types.

- Transportation Messages (TM)
- Mailing Messages (MM)
- Data Distribution Messages (DD)
- Dynamic Payment Template Messages
- Identification Messages (ID)
- Supply Chain Messages (SC)
- Informed Visibility (IV)
- System Messages
- Base: Shared simple types
- Definitions: Shared complex types and elements

The simple types shared across 2 or more modules are found in the Base schema. Likewise, the shared definitions module contains complex type definitions and elements that are shared across 2 or more modules.

Mail.XML Module Versioning Rules

The following versioning rules will be followed:

The Mail.XML wrapper schema**(.xsd) will always be given the next higher version number (or Errata designation) when any update is made to base, defs or any module. The name of the .xsd file will indicate the new version and the new version number will be used in the namespace and target declarations:

`xmlns:mailxml=http://delivery-tech.org/Specs/mailxml25.1/mailxml targetNamespace=http://delivery-tech.org/Specs/mailxml25.1/mailxml`

- When updates are made, only those modules that are updated will be given the next higher version number (or Errata letter designation).
- If updates are made to the base or defs, then the base and defs xsds will be given the next higher version number (or Errata designation) and all modules that call to them will also be given the next higher version number (or Errata designation).

For example:

- If the wrapper version is labeled as `xmlns:mailxml="http://deliverytech.org/Specs/mailxml25.1A/mailxml"` then at least one of the XSDs is at same version such as filename `= 'Mail.XML_25.1A.xsd' <- Errata A`
- If the wrapper version is labeled as `xmlns:mailxml="http://deliverytech.org/Specs/mailxml25.1B/mailxml"` then at least one of the XSDs is at same version such as filename `= 'Mail.XML_25.1B.xsd' <- Errata B`
- If the wrapper version is labeled as `xmlns:mailxml="http://deliverytech.org/Specs/mailxml25.1/mailxml"` then at least one of the XSDs is at same version such as filename `= 'Mail.XML_25.1.xsd' <- Major Version`

What's New in Mail.XML Version 25.1?

With this release, the Mail.XML Messaging Protocol moves to Version 25.1. This release supports structure changes required by mailing industry and Postal Service.

Changes supported by Mail.XML 25.1 include:

- CR 2510 - Proposal to update the campaignDataType complex type to be consistent with the USPS Informed Delivery product.
- CR 2508 / 2413 - Proposal to remove ServiceCodeType value of SA for Fragile and update the value description list. The service will not be supported by USPS
- CR 2509 / 2414 - Proposal to update and Add Rate Category values to support Containerizations Discount for USPS Marketing Mail Flats
- CR 2511 / 2415 - Proposal to update and Add Rate Category values to support Package Service Parcel Select Ground Cubic pricing

Mail.XML 25.1 XSD Modules:

The following Mail.XML XSD modules/namespaces are used:

Note: Actual xsd filenames include the version number (e.g. *mailxml_base_25.1.xsd*).

- mailxml_tm.xsd: This module contains all the transportation (or FAST) messages and the attributes, elements and complex types that are unique to these messages. Namespace=mailxml_tm:
- mailxml_mm.xsd: This module contains all the mailing messages (eDoc) and the attributes, elements and complex types that are unique to these messages. Namespace=mailxml_mm:
- mailxml_iv.xsd: This module contains informed visibility messages and the attributes, elements and complex types that are unique to these messages. Namespace=mailxml_iv:
- mailxml_dd.xsd: This module contains all the data distribution messages and the attributes, elements and complex types that are unique to these messages. Namespace=mailxml_dd:
- mailxml_id.xsd: This module contains all the identification messages and the attributes, elements and complex types that are unique to these messages. Namespace=mailxml_id:
- mailxml_sc.xsd: This module contains all the supply chain messages and the attributes, elements and complex types that are unique to these messages. Namespace=mailxml_sc:
- mailxml_defs.xsd: This module contains all the common definitions of attributes, elements and mailxml_base.xsd: This module contains simple types that are shared across two or more modules that make up Mail.XML. These can be considered a building block for any message group. Namespace=mailxml_base:
- mailxml.xsd: This module contains the system messages of Mail.XML and is used to build custom profiles for Mail.XML. Namespace=mailxml:

The Mail.XML™ 25.1 Messaging Documentation Set

The Mail.XML Messaging Specification has been organized into a set of documents. This *Schemas Specification* is one document in a set of documents that make up the Mail.XML Specification 25.1. Updates in this Specification are NOT backwardly compatible with previous versions. Other documents in the specification set include:

- Mail.XML™ 25.1: Transportation Messaging Specification documents all transportation messages

- Mail.XML™ 25.1: Mailing Messaging Specification documents all mailing messages
- Mail.XML™ 25.1: Informed Visibility Specification documents all informed visibility messages
- Mail.XML™ 25.1: Data Distribution Messaging Specification documents all data distribution messages
- Mail.XML™ 25.1: Identification Messaging Specification documents all identification messages
- Mail.XML™ 25.1: Supply Chain Messaging Specification documents all supply chain messages
- Mail.XML™ 25.1: System Messaging Specification documents all systems and fault messages
- Mail.XML™ 25.1: Simple Types Specification documents all simple types used across Mail.XML messages
- Mail.XML™ 25.1: Common Definitions Specification documents all shared elements and complex types.
- Mail.XML™ 25.1: Schemas contains the .XSDs that make up the Mail.XML Messaging Specification

Contents

Abstract.....	3
About Mail.XML™	3
About Mail.XML Schema Modularization	3
Mail.XML Module Versioning Rules.....	4
What’s New in Mail.XML Version 25.1?	5
Mail.XML 25.1 XSD Modules:	5
The Mail.XML™ 25.1 Messaging Documentation Set	5
Index	8
Elements – Complex Types – Simple Types	9

Index

Schema mailxml_id_25.1.xsd

schema location: [../XSD/mailxml_id_25.1.xsd](http://delivery-tech.org/Specs/mailxml25.1/mailxml_id_25.1.xsd)
attribute form default: **qualified**
element form default: **qualified**
targetNamespace: **http://delivery-tech.org/Specs/mailxml25.1/mailxml_id**

Elements

[CastofCharactersCancelRequest](#)
[CastofCharactersCancelResponse](#)
[CastofCharactersCreateRequest](#)
[CastofCharactersCreateResponse](#)
[CastofCharactersUpdateRequest](#)
[CastofCharactersUpdateResponse](#)
[CustomerRelationIdentifyQueryRequest](#)
[CustomerRelationIdentifyQueryResponse](#)
[CustomerRelationIdentifyUpdateRequest](#)
[CustomerRelationIdentifyUpdateResponse](#)
[IncentiveEnrollmentCreateRequest](#)
[IncentiveEnrollmentCreateResponse](#)
[USPSCRIDCreateValidateRequest](#)
[USPSCRIDCreateValidateResponse](#)
[USPSMIDCreateValidateRequest](#)
[USPSMIDCreateValidateResponse](#)

Complex types

[CofCCreateAcceptType](#)
[CofCCreateRejectType](#)
[cridCreateResponseType](#)
[CRIDEntryType](#)
[cridQueryResponseType](#)
[cRIDsRequestedType](#)
[cridValidateResponseType](#)
[customerIdentityType](#)
[groupContainerIDType](#)
[IncentiveEnrollmentEntryType](#)
[legalAcknowledgementBlockCRIDType](#)
[legalAcknowledgementBlockMIDType](#)
[legalAcknowledgementBlockMSPSType](#)
[mailPieceGroupCreateType](#)
[mailPieceGroupResponseType](#)
[midCreateResponseType](#)
[midEntryType](#)
[midQueryResponseType](#)
[midValidateResponseType](#)

Simple types

[MIDorCRIDRequestType](#)

Elements – Complex Types – Simple Types

element **CastofCharactersCancelRequest**

diagram	<p>CastofCharactersCancelRequest</p> <p>Message requesting the cancellation of unique identification the various roles for parties within the industry for a list to enable information access and sharing between USPS and multiple mailers.</p> <p>attributes</p> <ul style="list-style-type: none"> grp mailxml_defs:MailXMLHea... <ul style="list-style-type: none"> mailxml_id:SubmittingParty mailxml_id:SubmittingSoftware mailxml_id:SubmitterTrackingID mailxml_id:Participant (1..∞) mailxml_id:Role (1..∞) mailxml_id:UserLicenseCode mailxml_id:MaildatJobID mailxml_id:CustomerGroupID mailxml_id:MailingGroupID mailxml_id:MailPieceGroup (1..∞) mailxml_id:ContainerGroup (1..∞) mailxml_id:EffectiveDate mailxml_id:ExpirationDate mailxml_id:Duration mailxml_id:DurationUnitofMeasu...
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:SubmittingParty mailxml_id:SubmittingSoftware mailxml_id:SubmitterTrackingID mailxml_id:Participant mailxml_id:Role mailxml_id:UserLicenseCode mailxml_id:MaildatJobID mailxml_id:CustomerGroupID mailxml_id:MailingGroupID mailxml_id:MailPieceGroup mailxml_id:ContainerGroup mailxml_id:EffectiveDate mailxml_id:ExpirationDate mailxml_id:Duration mailxml_id:DurationUnitofMeasure
annotation	<p>documentation</p> <p>Message requesting the cancellation of unique identification the various roles for parties within the industry for a list to enable information access and sharing between USPS and multiple mailers.</p>

element **CastofCharactersCancelResponse**

diagram	<p>Response to a message requesting the cancellation of unique identification the various roles for parties within the industry.</p>
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:TrackingID mailxml_id:SubmitterTrackingID mailxml_id:CastofCharactersCancelAccept mailxml_id:CastofCharactersCancelReject
annotation	<p>documentation</p> <p>Response to a message requesting the cancellation of unique identification the various roles for parties within the industry.</p>

element **CastofCharactersCreateRequest**


diagram	<p>CastofCharactersCreateRequest</p> <p>Message requesting the creation of unique identification the various roles for parties within the industry for a list to enable information access and sharing between USPS and multiple mailers.</p>
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:SubmittingParty mailxml_id:SubmittingSoftware mailxml_id:SubmitterTrackingID mailxml_id:Participant mailxml_id:Role mailxml_id:UserLicenseCode mailxml_id:MaildatJobID mailxml_id:CustomerGroupID mailxml_id:MailingGroupID mailxml_id:MailPieceGroup mailxml_id:ContainerGroup mailxml_id:EffectiveDate mailxml_id:ExpirationDate mailxml_id:Duration mailxml_id:DurationUnitofMeasure
annotation	<p>documentation</p> <p>Message requesting the creation of unique identification the various roles for parties within the industry for a list to enable information access and sharing between USPS and multiple mailers.</p>

element **CastofCharactersCreateResponse**

diagram	<p>CastofCharactersCreateRespo... Response to a message requesting the creation of unique identification the various roles for parties within the industry.</p> <p>attributes</p> <ul style="list-style-type: none"> grp mailxml_defs:MailXMLHea... <ul style="list-style-type: none"> mailxml_defs:CustomerGroupID mailxml_defs:MailingGroupID mailxml_defs:MaildatJobID mailxml_defs:UserLicenseCode <p>mailxml_id:TrackingID</p> <p>mailxml_id:SubmitterTrackingID</p> <p>mailxml_id:CastofCharactersCr...</p> <p>mailxml_id:CastofCharactersCr...</p>
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:TrackingID mailxml_id:SubmitterTrackingID mailxml_id:CastofCharactersCreateAccept mailxml_id:CastofCharactersCreateReject
annotation	<p>documentation</p> <p>Response to a message requesting the creation of unique identification the various roles for parties within the industry.</p>

element **CastofCharactersUpdateRequest**

diagram



namespace http://delivery-tech.org/Specs/mailxml25.1/mailxml_id

children **mailxml_id:SubmittingParty mailxml_id:SubmittingSoftware mailxml_id:SubmitterTrackingID mailxml_id:Participant mailxml_id:Role mailxml_id:UserLicenseCode mailxml_id:MaildatJobID mailxml_id:CustomerGroupID mailxml_id:MailingGroupID mailxml_id:MailPieceGroup mailxml_id:ContainerGroup mailxml_id:EffectiveDate mailxml_id:ExpirationDate mailxml_id:Duration mailxml_id:DurationUnitofMeasure**

annotation documentation
Message requesting an update to unique identification the various roles for parties within the industry for a list to enable information access and sharing between USPS and multiple mailers.

element CastofCharactersUpdateResponse

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:TrackingID mailxml_id:SubmitterTrackingID mailxml_id:CastofCharactersUpdateAccept mailxml_id:CastofCharactersUpdateReject
annotation	documentation Response to a message requesting an update to unique identification the various roles for parties within the industry.

element CustomerRelationIdentifyQueryRequest

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:SubmittingParty mailxml_id:SubmittingSoftware mailxml_id:SubmitterTrackingID
annotation	documentation Query request for mail piece customer identifiers.

element **CustomerRelationIdentifyQueryResponse**

diagram	<p>The diagram illustrates the structure of the CustomerRelationIdentifyQueryResponse element. It features a main box labeled CustomerRelationIdentifyQuer... with the description "Response to the Query request for mail piece customer identifiers." This box is connected to a group of elements:</p> <ul style="list-style-type: none"> An attributes container (indicated by a square icon) which contains a group labeled grp mailxml_id:CRQueryRespo.... This group includes four attributes: mailxml_id:MaildatJobID, mailxml_id:MPUID, mailxml_id:SegmentID, and mailxml_id:ComponentID. A sequence container (indicated by a circle with three dots) which contains: <ul style="list-style-type: none"> A dashed box containing mailxml_id:TrackingID and mailxml_id:SubmitterTrackingID. An optional container (indicated by a circle with a plus sign) which contains two elements: mailxml_id:QueryResults and mailxml_defs:QueryError. The mailxml_defs:QueryError element has a description: "Error issued when the query data cannot be provided."
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:TrackingID mailxml_id:SubmitterTrackingID mailxml_id:QueryResults mailxml_defs:QueryError
annotation	<p>documentation</p> <p>Response to the Query request for mail piece customer identifiers.</p>

element CustomerRelationIdentifyUpdateRequest

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:SubmittingParty mailxml_id:SubmittingSoftware mailxml_id:SubmitterTrackingID mailxml_id:UpdateCustomerInfo
annotation	documentation Request to update mail piece customer information.

element CustomerRelationIdentifyUpdateResponse

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:TrackingID mailxml_id:SubmitterTrackingID mailxml_id:CustomerRelationIdentifyUpdateAccept mailxml_id:CustomerRelationIdentifyUpdateReject
annotation	documentation Response for the update request for mail piece customer information.

element IncentiveEnrollmentCreateRequest

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:SubmittingParty mailxml_id:SubmittingSoftware mailxml_id:SubmitterTrackingID mailxml_id:MSPIndicator mailxml_id:IncentiveEnrollmentEntry mailxml_id:Incentive
annotation	documentation Request to USPS to create Incentive Enrollment information.

element IncentiveEnrollmentCreateResponse

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:TrackingID mailxml_id:SubmitterTrackingID mailxml_id:MSPIndicator mailxml_id:SubmitterCRID mailxml_id:IncentiveEnrollmentCreateAccept mailxml_id:IncentiveEnrollmentCreateReject
annotation	documentation Response to a request to USPS to create Incentive Enrollment information.

element **USPSCRIDCreateValidateRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:SubmittingParty mailxml_id:SubmittingSoftware mailxml_id:SubmitterTrackingID mailxml_id:CRIDRequestType mailxml_id:CRIDEntry
annotation	documentation Request to the USPS to create or validate one or more CRIDs.

element **USPSCRIDCreateValidateResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:TrackingID mailxml_id:SubmitterTrackingID mailxml_id:USPSCRIDCreateResponse mailxml_id:USPSCRIDQueryResponse mailxml_id:USPSCRIDValidateResponse
annotation	documentation Response to a request to the USPS to query, create, or validate one or more CRIDs.

element **USPSMIDCreateValidateRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:SubmittingParty mailxml_id:SubmittingSoftware mailxml_id:SubmitterTrackingID mailxml_id:MIDRequestType mailxml_id:MIDEntry
annotation	documentation Request to USPS to create or validate MID information.

namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:SubmittingParty mailxml_id:SubmittingSoftware mailxml_id:SubmitterTrackingID mailxml_id:MIDRequestType mailxml_id:MIDEntry
annotation	documentation Request to USPS to create or validate MID information.

element USPSMIDCreateValidateResponse

diagram	<p>Response to a request to USPS to query, create, or validate MID information.</p>
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:TrackingID mailxml_id:SubmitterTrackingID mailxml_id:USPSMIDCreateResponse mailxml_id:USPSMIDQueryResponse mailxml_id:USPSMIDValidateResponse
annotation	documentation Response to a request to USPS to query, create, or validate MID information.

complexType CofCCreateAcceptType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:UserLicenseCode mailxml_id:MaildatJobID mailxml_id:CustomerGroupID mailxml_id:MailingGroupID mailxml_id:ContainerGroup mailxml_id:MailPieceGroup mailxml_id:ReturnInfo
used by	element CastofCharactersCreateResponse/CastofCharactersCreateAccept

complexType CofCCreateRejectType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:UserLicenseCode mailxml_id:MaildatJobID mailxml_id:CustomerGroupID mailxml_id:MailingGroupID mailxml_id:ContainerGroup mailxml_id:MailPieceGroup mailxml_id:ReturnInfo
used by	element CastofCharactersCreateResponse/CastofCharactersCreateReject

complexType cridCreateResponseType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:USPSCRIDCreateAccept mailxml_id:USPSCRIDCreateReject
used by	element USPSCRIDCreateValidateResponse/USPSCRIDCreateResponse

complexType CRIDEntryType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:CRID mailxml_id:CompanyName mailxml_id:PermitPublicationData mailxml_id:CompanyHQIndicator mailxml_id:Address mailxml_id:AddressMatch mailxml_id:ApplyingForSelf mailxml_id:LegalAcknowledgementBlock
used by	elements USPSCRIDCreateValidateRequest/CRIDEntry cridCreateResponseType/USPSCRIDCreateAccept/CRIDEntry cridCreateResponseType/USPSCRIDCreateReject/CRIDEntry cridQueryResponseType/USPSCRIDQueryAccept/CRIDEntry cridQueryResponseType/USPSCRIDQueryReject/CRIDEntry cridValidateResponseType/USPSCRIDValidateAccept/CRIDEntry cridValidateResponseType/USPSCRIDValidateReject/CRIDEntry

complexType cridQueryResponseType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:USPSCRIDQueryAccept mailxml_id:USPSCRIDQueryReject
used by	element USPSCRIDCreateValidateResponse/USPSCRIDQueryResponse

complexType cRIDsRequestedType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:CRID mailxml_id:CompanyName mailxml_id:Address mailxml_id:PermitPublicationData mailxml_id:ApplyingForSelf mailxml_id:LegalAcknowledgementBlock

complexType cridValidateResponseType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:USPSCRIDValidateAccept mailxml_id:USPSCRIDValidateReject
used by	element USPSCRIDCreateValidateResponse/USPSCRIDValidateResponse

complexType customerIdentityType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
used by	elements CustomerRelationIdentifyQueryResponse/QueryResults/CustomerID CustomerRelationIdentifyUpdateResponse/CustomerRelationIdentifyUpdateAccept/SetCustomerInfo CustomerRelationIdentifyUpdateRequest/UpdateCustomerInfo
annotation	documentation Structure describpg the customer information

complexType groupContainerIDType


diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:MaildatContainer mailxml_id:MailXMLContainer mailxml_id:ContainerBarcode
used by	elements CastofCharactersCancelRequest/ContainerGroup CastofCharactersCreateRequest/ContainerGroup CastofCharactersUpdateRequest/ContainerGroup CofCCreateAcceptType/ContainerGroup CofCCreateRejectType/ContainerGroup

complexType IncentiveEnrollmentEntryType


diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:CustomerCRID mailxml_id:CustomerName mailxml_id:PermitPublicationData mailxml_id:CompanyHQIndicator mailxml_id:Address1 mailxml_id:Address2 mailxml_id:City mailxml_id:State

	mailxml_id:ZipCode mailxml_id:SequenceNumber mailxml_id:EnrollingForSelf mailxml_id:LegalAcknowledgementBlock	
used by	elements	IncentiveEnrollmentCreateRequest/IncentiveEnrollmentEntry IncentiveEnrollmentCreateResponse/IncentiveEnrollmentCreateAccept/IncentiveEnrollmentEntry IncentiveEnrollmentCreateResponse/IncentiveEnrollmentCreateReject/IncentiveEnrollmentEntry


complexType legalAcknowledgementBlockCRIDType

diagram		
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id	
children	mailxml_id:UnderstandLegalLiabilityForApplyingForSomeOneElse mailxml_id:AcknowledgeNotifyingTheMailOwner mailxml_id:USPSLegalAgreement	
used by	elements	cRIDsRequestedType/LegalAcknowledgementBlock CRIDEntryType/LegalAcknowledgementBlock

complexType legalAcknowledgementBlockMIDType

diagram		
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id	
children	mailxml_id:UnderstandLegalLiabilityForApplyingForSomeOneElse mailxml_id:AcknowledgeNotifyingTheMailOwner mailxml_id:USPSLegalAgreement	
used by	element	midEntryType/LegalAcknowledgementBlock

complexType legalAcknowledgementBlockMSPSType

diagram		
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id	
children	mailxml_id:UnderstandLegalLiabilityForApplyingForSomeOneElse mailxml_id:AcknowledgeNotifyingTheMailOwner mailxml_id:MSPSLegalAgreement	
used by	element	IncentiveEnrollmentEntryType/LegalAcknowledgementBlock


complexType mailPieceGroupCreateType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:MailPieceID mailxml_id:LowestMailPieceID mailxml_id:HighestMailPieceID
used by	elements CastofCharactersCancelRequest/MailPieceGroup CastofCharactersCreateRequest/MailPieceGroup CastofCharactersUpdateRequest/MailPieceGroup CofCCreateAcceptType/MailPieceGroup CofCCreateRejectType/MailPieceGroup

complexType mailPieceGroupResponseType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:SubmitterTrackingID mailxml_id:TrackingID mailxml_id:MailPieceID mailxml_id:LowestMailPieceID mailxml_id:HighestMailPieceID


complexType midCreateResponseType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:USPSMIDCreateAccept mailxml_id:USPSMIDCreateReject
used by	element USPSMIDCreateValidateResponse/USPSMIDCreateResponse

complexType midEntryType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:MID mailxml_id:CustomerCRID mailxml_id:CustomerName mailxml_id:PermitPublicationData mailxml_id:CompanyHQIndicator mailxml_id:Address mailxml_id:SequenceNumber mailxml_id:ApplyingForSelf mailxml_id:LegalAcknowledgementBlock
used by	elements USPSMIDCreateValidateRequest/MIDEntry midCreateResponseType/USPSMIDCreateAccept/MIDEntry midCreateResponseType/USPSMIDCreateReject/MIDEntry midQueryResponseType/USPSMIDQueryAccept/MIDEntry midQueryResponseType/USPSMIDQueryReject/MIDEntry midValidateResponseType/USPSMIDValidateAccept/MIDEntry midValidateResponseType/USPSMIDValidateReject/MIDEntry

complexType midQueryResponseType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:USPSMIDQueryAccept mailxml_id:USPSMIDQueryReject

used by	element USPSMIDCreateValidateResponse/USPSMIDQueryResponse
---------	---

complexType **midValidateResponseType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
children	mailxml_id:USPSMIDValidateAccept mailxml_id:USPSMIDValidateReject
used by	element USPSMIDCreateValidateResponse/USPSMIDValidateResponse

simpleType **MIDorCRIDRequestType**

namespace	http://delivery-tech.org/Specs/mailxml25.1/mailxml_id
type	restriction of xs:string
used by	elements USPSCRIDCreateValidateRequest/CRIDRequestType USPSMIDCreateValidateRequest/MIDRequestType